

Multi-1/micro USB RS232

USB to Serial Converter



Multi-1/micro USB RS232 is a USB to Serial converter which adds RS232 serial port using micro USB Type ports on smartphones and tablets. PnP function of USB supports easy installation/removal and LED as an indicator for the communication status making it easy to check the operation from outside.

Specification

15KV Surge Protector

Multi-1/micro USB has a built in 15k V surge protecting function, preventing circuit breakage from ESD or external surges. This prevents the product malfunction or damage due to electric shocks.

Micro USB Type B Connector

Multi-1/micro USB supports micro USB connector, which are widely used in Android smartphones and tablets. This enables serial communication through USB port on smartphones and tablets.

TX/RX LED

Communication error and operation status can be intuitively identified through LED.

Multi-1/micro USB RS232 Specification Sheet

USB	USB I/F	USB 2.0
	Connector Type	Micro USB Type B
Serial	Standard	RS232
	Serial Port	DB9 Male
	Number of ports	1
	Baud Rate	Max. 921.6kbps
	Signals(RS232)	RS232: TXD, RXD, RTS, CTS, DTR, DSR, DCD, RI
	Parity bit	None, Even, Odd
	Flow control	RTS/CTS, XON/XOFF
	Protection	±15kV ESD Protection
Hardware & Environment	LED	Tx(Green), Rx(Red)
	Dimension(W x L x H)	49 x 39 x 16.3mm
	Weight	40g
	Operating Temperature	-20 ~ 70℃
	Storage Temperature	-20 ~ 70℃
Software	Humidity	5~95% Non-condensing
	OS Support(Driver)	Android OS 3.2 or above
Ordering information(RS232)		Multi-1/micro USB RS232

© SystemBase Co., Ltd.

16F Daerung Post Tower-1, Digital-ro 288, Guro-gu, Seoul, Republic of Korea 08390


Tel +82-2-855-0501 | Fax +82-2-855-0580 | www.sysbas.com

Specifications subject to change without notice



Multi-1/micro USB RS232 Specification Sheet

Pin Spec _____



<RS232>

© SystemBase Co., Ltd.

16F Daerung Post Tower-1, Digital-ro 288, Guro-gu, Seoul, Republic of Korea 08390


Tel +82-2-855-0501 | Fax +82-2-855-0580 | www.sysbas.com

Specifications subject to change without notice



Multi-1/micro USB RS232 Specification Sheet

Dimension



unit: mm

© SystemBase Co., Ltd.

16F Daerung Post Tower-1, Digital-ro 288, Guro-gu, Seoul, Republic of Korea 08390

Tel +82-2-855-0501 | Fax +82-2-855-0580 | www.sysbas.com

Specifications subject to change without notice

